



Product Data

Static Dissipative PU Boot

Model : TAU - 9470

Code : 2502 Series



Physical Properties

Material	Upper	PU
	Sole	PU

Electrical Properties

Point to point resistance, fabric upper	$1.0 \times 10^5 - 1.0 \times 10^9$	Ohm
Resistance to ground, inner sole	$1.0 \times 10^5 - 1.0 \times 10^9$	Ohm
Surface resistance, outer sole	$1.0 \times 10^6 - 5.0 \times 10^8$	Ohm

Sizes Available

Size	230, 240, 250, 260, 270, 280, 290
------	-----------------------------------

Washing Requirement

Washing Temperature	40	°C
Drying Temperature	< 70	°C

Fabric

Pro-Pack customize legging to suit customer requirement. Please refer to Fabric Chart or Sales Engineer for more details.

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18
Toa Payoh Industrial Estate
Singapore 318992

Tel : +65 63541511
Fax : +65 63541711
Email : sales@pro-pack.com.sg
Website : www.pro-pack.com.sg

Regional Offices :

Malaysia
Bold Pack Industries Sdn Bhd

Indonesia
PT Pro-Pack Industries

Thailand
Bold-Pack Materials (Thai) Co. Ltd

Philippines
Pro-Pack Materials (Philippines) Inc.

India
Pro-Pack Materials India Pvt Ltd

China
Pro-Pack Materials (Wuxi) Co., Ltd