

Product Data

ESD Soldering Station

Model : 236 ESD

Code: 4003 series



Features

Ceramic heater has a long lifetime.

Ceramic heater has a long lifetime.

Calibrate temperature digitally.

New appearance and firm structure.

Various types of tips are available.

ESD safe design.

It is especially suitable for mounting and reworking SMD components by hand, soldering common and directly-inserted electronics, or lead free soldering under other special conditions.

Technical Specification

Power consumption	90W
Temperature range	80 °C - 480 °C
Temperature stability	+/- 2 °C (Stationary air, no load)
Ambient Temperature (Max)	40 °C
Heater operating voltage	30V AC
Tip to ground potential	<2mV
Tip to ground resistance	< 2 Ω
Length of wire	1.2 meter
Length of handle only (Without wire)	190 mm
Dimensions	160 (L) x 105 (W) x 125 (H) mm
Weight	About 2.6 kg

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18 Toa Payoh Industrial Estate Singapore 318992

Tel : +65 63541511 Fax : +65 63541711 Email : sales@pro-pack.com.sg Website : www.pro-pack.com.sg

Regional Offices :

Malaysia Bold Pack Industries Sdn Bhd

Indonesia PT Pro-Pack Industries

Thailand Bold-Pack Materials (Thai) Co. Ltd

Philippines Pro-Pack Materials (Philippines) Inc.

India Pro-Pack Materials India Pvt Ltd

China Pro-Pack Materials (Wuxi) Co., Ltd



Product Data

ESD Soldering Station

Model : Oriteq 969

Code: 4003-0043

Replaceable Soldering Tips

960-T-1.2L)	
0047) 012 012	>	
⊥⊥ 0.7(0.028)	25(0.98)	
960-T-B		
\odot	R0.5(0.02)	
	17(0.66)	
960-T-LB		
RO	.2(0.008)	
	25(0.98)	
960-T-I	Do 2/0 009)	
\bigcirc	R0.2(0.008)	
Ó		
	17(0.66)	8
960-T-0.8C		
() E8		
(10031) 20.8		
	45° 17(0.66)	

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18 Toa Payoh Industrial Estate Singapore 318992

 Tel
 : +65 63541511

 Fax
 : +65 63541711

 Email
 : sales@pro-pack.com.sg

 Website : www.pro-pack.com.sg

Regional Offices :

Malaysia Bold Pack Industries Sdn Bhd

Indonesia PT Pro-Pack Industries

Thailand Bold-Pack Materials (Thai) Co. Ltd

Philippines Pro-Pack Materials (Philippines) Inc.

India Pro-Pack Materials India Pvt Ltd

China Pro-Pack Materials (Wuxi) Co., Ltd

960-T-1C $ \begin{array}{c} $
960-T-1CF* 960-T-2C
960-T-1CF* 15(0.6) 960-T-2C ⓐ ⓐ ⓑ ↓ 17(0.65)
45 17/0 66)
17(0.66)
960-T-2CF*
960-T-3C
960-T-3CF* 17(0.66)
960-T-4C
960-T-4CF* 17(0.66)
960-T-K