

Product Data

Glove, PU Conductive

Code : 5106 Series



Physical Properties

Palm	Polyester Laminated PU		
Construction	Polyester	70	%
	PU	30	%
Back	Polyester weave with Conductive Yarn		
Construction	Polyester	99	%
	Conductive Yarn	1	%

Electrical Properties

Surface Resistivity	$1 \times 10^5 - 1 \times 10^9$	Ohm / sq
Tribo-Charge	< 100	V
Testing Temperature	20	°C
Relative Humidity	50 - 60	%

Dimension	Length	Width	
Small	206 +/- 5	88 +/- 3	mm
Medium	213 +/- 5	95 +/- 3	mm
Length	220 +/- 5	100 +/- 3	mm

Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18
Toa Payoh Industrial Estate
Singapore 318992

Tel : +65 63541511
Fax : +65 63541711
Email : sales@pro-pack.com.sg
Website : www.pro-pack.com.sg

Regional Offices :

Malaysia
Bold Pack Industries Sdn Bhd

Indonesia
PT Pro-Pack Industries

Thailand
Bold-Pack Materials (Thai) Co. Ltd

Philippines
Pro-Pack Materials (Philippines) Inc.

India
Pro-Pack Materials India Pvt Ltd

China
Pro-Pack Materials (Wuxi) Co., Ltd