

## Product Data

### Conductive Mat

Code : 5318 Series



#### Material

Homogenous Layer	Conductive rubber
Surface	Non shinning, shinning

#### Colour

Colour	Black
--------	-------

#### Electrical Properties

Tensile Strength	Width	105	Kg/cm <sup>2</sup>	KS M 6518-91
	Length	114		
Elongation	Width	380	%	
	Length	370		
Hardness	Length	64	HS	
Tear Strength (B)	Width	31	Kg/cm	
	Length	37		
Temperature Resistance		Max.130	°C	
Surface Resistivity	Black	10 <sup>3</sup> - 10 <sup>5</sup>	Ohm/sqmt	ASTM D257
Volume Resistivity	Black	10 <sup>4</sup> - 10 <sup>6</sup>	Ohm/sqmt	ASTM D257
Static Decay 5 Kv - 500v		<0.01	Sec	FTS 101C

#### Size

Length	10, 20	m
Width	60, 90, 100 , 120	cm
Thickness	2, 3	mm

#### Pro-Pack Materials Pte Ltd

Blk 970, Toa Payoh North, #04-18  
Toa Payoh Industrial Estate  
Singapore 318992

Tel : +65 63541511  
Fax : +65 63541711  
Email : sales@pro-pack.com.sg  
Website : www.pro-pack.com.sg

#### Regional Offices :

**Malaysia**  
Bold Pack Industries Sdn Bhd

**Indonesia**  
PT Pro-Pack Industries

**Thailand**  
Bold-Pack Materials (Thai) Co. Ltd

**Philippines**  
Pro-Pack Materials (Philippines) Inc.

**India**  
Pro-Pack Materials India Pvt Ltd

**China**  
Pro-Pack Materials (Wuxi) Co., Ltd